



CAMERON GREAT LAKES, INC.

MOLECULAR FILTRATION SPECIALISTS

CGL CP48

DESCRIPTION:

CP 48 is a bituminous coal based 4 mm pelletized activated carbon of high adsorptive capacity. It has a well developed pore structure for the adsorption of a wide range of volatile organic compounds.

APPLICATIONS:

It is ideally suited for critical applications such a process gas purification, solvent vapor recovery and catalyst support.

Physical Properties

ACTIVITY for CCL ₄ , (ASTM D3467-94)	60, minimum
BULK DENSITY , TYPICAL	26-28 lbs / cu ft
HARDNESS , (ASTM D3808-79)	98, min
MOISTURE , AS PACKED, (ASTM D2867-95)	2 %
ASH CONTENT , TYPICAL	10 - 12 %

This information has been gathered from standard reference materials and/or test procedures and is believed to be true and accurate. It is offered solely for your consideration and verification. None of the information presented shall be construed as constituting a warranty or representation, expressed, write, or implied, for which we assume legal responsibility or that the information or goods described is fit for any particular use either alone or in combination with other goods or processes, or that its use does not conflict with existing patent rights. No license is granted to infringe on any patent rights or practice any patent inversion.

2335 NW 29TH AVENUE, PORTLAND, OR 97210
PHONE: (800) 777-4044 FAX: (503) 225-0137

WWW.CAMERONGREATLAKES.COM
EMAIL: SALES@CGLCARBON.COM