



CAMERON GREAT LAKES, INC.

MOLECULAR FILTRATION SPECIALISTS

CGL/PA

DESCRIPTION: CGL/PA is a high activity, specially impregnated activated carbon. It is available on both coconut shell and coal pellet.

APPLICATIONS: Removal of ammonia and amines in vapor phase applications.

PHYSICAL PROPERTIES:

BASE MATERIAL	
ACTIVITY FOR CCL ₄ (ASTM D-3467)	60%
BULK DENSITY, TYPICAL	30 LBS/CU FT.
BALL PAN HARDNESS (ASTM D3082-79)	95 MINIMUM
FINISHED PRODUCT	
BULK DENSITY, TYPICAL	35 LBS/CU FT.
AMMONIA (NH ₃) REMOVAL	7 %*

* Equals 30% of the weight of the base of activated carbon before treatment.

This information has been gathered from standard reference materials and/or test procedures and is believed to be true and accurate. It is offered solely for your consideration and verification. None of the information presented shall be construed as constituting a warranty or representation, expressed, written, or implied, for which we assume legal responsibility or that the information or goods described is fit for any particular use either alone or in combination with other goods or processes, or that its use does not conflict with existing patent rights. No license is granted to infringe on any patent rights or practice any patent inversion.

2335 NW 29TH AVENUE, PORTLAND, OR 97210
PHONE: (800) 777-4044 FAX: (503) 225-0137

WWW.CAMERONGREATLAKES.COM
EMAIL: SALES@CGLCARBON.COM