

CAMERON GREAT LAKES, INC.

MOLECULAR FILTRATION SPECIALISTS

VAPORTRAP

DISPOSABLE V-BANK

FEATURES

- 36 pounds of activated carbon in a nominal 24" x 24" x 12".
- Pressure drop 0.45 iwg @ 2000 CFM.
- Revolutionary bulk fill, no honeycomb design.
- Total detention, no bypass
- Custom media fill available
- Suitable for initial and retrofit applications in both front and side access arrangements.
- Available in custom sizes, length, width and depths from 4" to 12" in both box and header styles.
- Initial efficiency greater than 95 % at rated air flow.
- Moisture resistant construction, allows for use where humidity and moisture are present.



APPLICATIONS

The Vapor Trap disposable v-bank filter is ideally suited for use in both commercial and industrial applications. It's unique design and versatility allows it to be an easy retrofit in any HVAC system, and custom OEM applications. The filter can be supplied as is or with a downstream dusting filter that is an integral part of the filter panel. Designed for high efficiency and long life, it is an economical solution for removal of various contaminants including, diesel fumes, smoke, unwanted food odors, chemical contaminants, outdoor and indoor air pollutants, formaldehyde and ozone.

HOSPITALS

AIRPORTS & CONTROL TOWERS

MUSEUMS & ARCHIVES

BARS & RESTAURANTS


SEMICONDUCTOR APPLICATIONS

INDUSTRIAL FACILITIES

Page 1 of 2

2335 NW 29TH AVENUE, PORTLAND, OR 97210
PHONE: (800) 777-4044 FAX: (503) 225-0137

WWW.CAMERONGREATLAKES.COM
EMAIL: SALES@CGLCARBON.COM



CAMERON GREAT LAKES, INC.

MOLECULAR FILTRATION SPECIALISTS

PERFORMANCE DATA

Model Number	Face Size, in	MAX: CFM	Cubic ft. of media	Carbon lbs	C/ZK6 lbs	Cell Weight, lbs (carbon)
VT242412	23.375 x 23.375	2000	1.2	36	50	53
VT24246	23.375 x 23.375	2000	0.6	18	25	27
VT24244	23.375 x 23.375	2000	0.4	12	16	18

NOTES

1. Standard depth is 11.31. Custom depths from 4" - 8" are available upon request.
2. Filters are available in box, single header, and double header styles.
3. Custom sizes are available.
4. All filters can be supplied with an optional downstream dusting filter.

SPECIFICATION GUIDE

CONSTRUCTION

- Adsorber shall be constructed of multiple media filled panels. Each 24 x 24 x 12 filter shall hold 12 panels arranged in a V-Bank configuration and sealed in a polished aluminum or galvanized frame.
- Individual panels shall be 0.75 inches thick and made of galvanized steel expanded metal with polypropylene supports. The polypropylene supports shall be spaced every 1 1/2" and angled to prevent any bypass.
- Standard media is 4 x 8 or 4 x 6 mesh.
- Panels shall be individually fastened to the frame. Frame shall be fully lined with gasket to prevent bypass.
- Vapor Trap filters shall be individually sealed in a plastic bag, and placed in individual cartons at the factory.

PERFORMANCE

- Standard carbon shall have a minimum 60% CTC activity per ASTM D-3467 test method.
- Standard ZK-6 shall have a minimum 6% potassium permanganate.
- A 24 x 24 x 12 inch Vapor Trap shall contain no less than 36 pounds of carbon and no less than 50 pounds of C/ZK-6 and no less than 72 pounds of ZK6.
- The air resistance on a 24 x 24 x 12 nominal shall be no more than 0.50 in. of WG when operating at 2000 CFM.
- Adsorber shall be designed for total detention gaseous contamination control.